

产品承认书
Specification For Approved

版本: REV.A00

客户名称/Customer name:	N/A
客户品名/Customer name:	N/A
客户型号/Customer Model number:	N/A
客户料号/Customer material number:	N/A
巨维品名/JW name:	Plastic inductors
巨维型号/JW Model number:	MRPC565040 Series
巨维料号/JW Material number:	N/A

巨维签署/JW Signed			客户承认/Customer Approval		
制定 Prepared By	审核 Checked By	批准 Approved By	确认 Confirm By	审核 Checked By	承认 Approved By
唐秀玲	王瑞琳	欧奇林			
2024.9.7	2024.9.7	2024.9.7			

公司地址: 深圳市宝安区西乡街道臣田工业区 34 栋奥芯创新研究院 3018 室
Address: Room 3018, Aoxin Innovation Research Institute, Building 34, Chentian Industrial Zone, Xixiang Street, Baoan District, Shenzhen

工厂地址: 中国 湖南省 衡阳市 衡山科学城 2-10栋
Address: Building 2-10, Hengshan Science City, Hengyang City, Hunan Province, China

JS-RD-SPEC-001/A0

深圳市巨维科技有限公司
Shenzhen Ju Wei Technology Co., Ltd

客户名称 Customer	N/A	品名 Name	Plastic inductors	版本 Ver.	A00
客户型号 Model No.	N/A	料号 Material No.	N/A	日期 Date	2024.9.7
客户料号 Customer No.	N/A	型号 Model No.	MRPC565040 Series	发行号 Release No.	JS-S-24090703


变更履历/Modify Record

版本 Ver.	变更内容/Change content	日期 Date	制定 Prepared By	审核 Checked By
A00	新发行/New release	2024.9.7	唐秀玲	王瑞琳

公司地址：深圳市宝安区西乡街道臣田工业区 34 栋奥芯创新研究院 3018 室
Address: Room 3018, Aoxin Innovation Research Institute, Building 34, Chentian Industrial Zone, Xixiang Street, Baoan District, Shenzhen
工厂地址：中国 湖南省 衡阳市 衡山科学城 2-10栋
Address: Building 2-10, Hengshan Science City, Hengyang City, Hunan Province, China

客户名称 Customer	N/A	品名 Name	Plastic inductors	版本 Ver.	A00
客户型号 Model No.	N/A	料号 Material No.	N/A	日期 Date	2024.9.7
客户料号 Customer No.	N/A	型号 Model No.	MRPC565040 Series	发行号 Release No.	JS-S-24090703

1. 产品形状尺寸(单位:毫米)/Product Shape size(Unit:mm):



A	B	C	E	F	G	H	I	J
5.6±0.3	5.0±0.2	4.0±0.3	4.0±0.1	0.7±0.1	1.10	4.50	2.00	4.00

2. 品名型号命名指南/Nomenclature guidelines for product models:

J - MRPC 565040 A - 2R2 M - X
① ② ③ ④ ⑤ ⑥ ⑦

①	公司名称代码/Company name code
J	巨晟电子代码/JUSHENG electronic code
②	产品系列代码/Product family code
MRPC	塑封电感/Plastic inductors
③	产品外形尺寸(毫米)/Product dimension(mm)
565040	长5.6*宽5.0*高4.0毫米/Length5.6 *Width5.0 *Height4.0mm
④	外观形状区分代码，请参考产品形状尺寸页面
A	Appearance shape distinguishes the code ,Please refer to the product shape and size page
⑤	电感量标识(亨利)/Inductance identification(H)
2R2	R22(0.22μH) , 2R2(2.2μH) , 100(10μH) , 221(220μH) , 202(2000μH)
⑥	电感容差字母代码/Inductance tolerance letter code
M	J±5% , K±10% , L±15% , M±20% , P±25% , N±30%
⑦	内部管理代码/Internal management code
X	无代码为常规产品，其它请咨询/No code regular product, other please consult

客户名称 Customer	N/A	品名 Name	Plastic inductors	版本 Ver.	A00
客户型号 Model No.	N/A	料号 Material No.	N/A	日期 Date	2024.9.7
客户料号 Customer No.	N/A	型号 Model No.	MRPC565040 Series	发行号 Release No.	JS-S-24090703

3. 耐温等级/Temperature resistance class:

工作温度: -40 ~ +125°C(含自温升)
Operating Temperature : -40 ~ +125°C(Including self - temperature rise)

4. 电气性能表/Electrical Characteristics List:

NO.	Part Number	电感值 Inductance (uH)	Q值 min.	测试频率 Test frequency L,Q (MHz)	自谐频率 Self- resonant frequency (MHz)min.	直流电阻 DC resistance (Ω) max.	额定电流 Rated current. (mA)max.	电感允差 Inductance tolerance
1	J-MRPC565040A-1R0X	1.0	10	7.960	95.0	0.030	1800.0	±10%, ±20%
2	J-MRPC565040A-1R2X	1.2	10	7.960	70.0	0.035	1700.0	±10%, ±20%
3	J-MRPC565040A-1R5X	1.5	10	7.960	55.0	0.040	1600.0	±10%, ±20%
4	J-MRPC565040A-1R8X	1.8	10	7.960	47.0	0.050	1400.0	±10%, ±20%
5	J-MRPC565040A-2R2X	2.2	10	7.960	42.0	0.060	1300.0	±10%, ±20%
6	J-MRPC565040A-2R7X	2.7	10	7.960	37.0	0.070	1200.0	±10%, ±20%
7	J-MRPC565040A-3R3X	3.3	10	7.960	34.0	0.080	1120.0	±10%, ±20%
8	J-MRPC565040A-3R9X	3.9	10	7.960	32.0	0.090	1050.0	±10%, ±20%
9	J-MRPC565040A-4R7X	4.7	10	7.960	29.0	0.110	950.0	±10%, ±20%
10	J-MRPC565040A-5R6X	5.6	10	7.960	26.0	0.130	880.0	±10%, ±20%
11	J-MRPC565040A-6R8X	6.8	10	7.960	24.0	0.150	810.0	±10%, ±20%
12	J-MRPC565040A-8R2X	8.2	10	7.960	22.0	0.180	750.00	±10%, ±20%
13	J-MRPC565040A-100X	10.0	10	2.520	19.0	0.210	690.0	±10%, ±20%
14	J-MRPC565040A-120X	12.0	10	2.520	17.0	0.250	630.0	±10%, ±20%
15	J-MRPC565040A-150X	15.0	10	2.520	16.0	0.300	580.0	±10%, ±20%
16	J-MRPC565040A-180X	18.0	10	2.520	14.0	0.360	530.0	±10%, ±20%
17	J-MRPC565040A-220X	22.0	10	2.520	13.0	0.430	480.0	±5%, ±10%

Test remarks:
1.Rated current: Value obtained when current flows and the temperature has risen to 20°C or when DC current flows and the initial value of inductance has fallen by 10%, whichever is smaller
2.Test equipment L, Q: HP4285A +16034E, or equivalent.
3.SRF: HP8753C NETWORK ANALYZER, or equivalent.
4.DC resistance: AX-111A DIGITAL MILLIOHM METER, or equivalent.

客户名称 Customer	N/A	品名 Name	Plastic inductors	版本 Ver.	A00
客户型号 Model No.	N/A	料号 Material No.	N/A	日期 Date	2024.9.7
客户料号 Customer No.	N/A	型号 Model No.	MRPC565040 Series	发行号 Release No.	JS-S-24090703

3. 耐温等级/Temperature resistance class:

工作温度: -40 ~ +125°C(含自温升)
Operating Temperature : -40 ~ +125°C(Including self - temperature rise)

4. 电气性能表/Electrical Characteristics List:

NO.	Part Number	电感值 Inductance (uH)	Q值 min.	测试频率 Test frequency L,Q (MHz)	自谐频率 Self- resonant frequency (MHz)min.	直流电阻 DC resistance (Ω) max.	额定电流 Rated current. (mA)max.	电感允差 Inductance tolerance
1	J-MRPC565040A-270X	27.0	10	2.520	11.50	0.520	440.0	±5%, ±10%
2	J-MRPC565040A-330X	33.0	10	2.520	10.50	0.620	400.0	±5%, ±10%
3	J-MRPC565040A-390X	39.0	10	2.520	9.50	0.720	370.0	±5%, ±10%
4	J-MRPC565040A-470X	47.0	10	2.520	8.50	0.850	340.0	±5%, ±10%
5	J-MRPC565040A-560X	56.0	10	2.520	7.80	1.000	310.0	±5%, ±10%
6	J-MRPC565040A-680X	68.0	10	2.520	7.00	1.200	290.0	±5%, ±10%
7	J-MRPC565040A-820X	82.0	10	2.520	6.40	1.400	270.0	±5%, ±10%
8	J-MRPC565040A-101X	100.0	20	0.796	6.00	1.600	250.0	±5%, ±10%
9	J-MRPC565040A-121X	120.0	20	0.796	5.40	1.900	230.0	±5%, ±10%
10	J-MRPC565040A-151X	150.0	20	0.796	4.80	2.200	210.0	±5%, ±10%
11	J-MRPC565040A-181X	180.0	20	0.796	4.40	2.800	190.0	±5%, ±10%
12	J-MRPC565040A-221X	220.0	20	0.796	3.90	3.400	170.00	±5%, ±10%
13	J-MRPC565040A-271X	270.0	20	0.796	3.60	4.200	155.0	±5%, ±10%
14	J-MRPC565040A-331X	330.0	20	0.796	3.20	4.900	140.0	±5%, ±10%
15	J-MRPC565040A-391X	390.0	20	0.796	2.90	5.800	130.0	±5%, ±10%
16	J-MRPC565040A-471X	470.0	20	0.796	2.60	7.000	120.0	±5%, ±10%
17	J-MRPC565040A-561X	560.0	20	0.796	2.40	8.500	110.0	±5%, ±10%

Test remarks:

1.Rated current: Value obtained when current flows and the temperature has risen to 20°C or when DC current flows and the initial value of inductance has fallen by 10%, whichever is smaller

2.Test equipment L, Q: HP4285A +16034E, or equivalent.

3.SRF: HP8753C NETWORK ANALYZER, or equivalent.

4.DC resistance: AX-111A DIGITAL MILLIOHM METER, or equivalent.

客户名称 Customer	N/A	品名 Name	Plastic inductors	版本 Ver.	A00
客户型号 Model No.	N/A	料号 Material No.	N/A	日期 Date	2024.9.7
客户料号 Customer No.	N/A	型号 Model No.	MRPC565040 Series	发行号 Release No.	JS-S-24090703

3. 耐温等级/Temperature resistance class:

工作温度: -40 ~ +125°C(含自温升)
Operating Temperature : -40 ~ +125°C(Including self - temperature rise)

4. 电气性能表/Electrical Characteristics List:

NO.	Part Number	电感值 Inductance (uH)	Q值 min.	测试频率 Test frequency L,Q (MHz)	自谐频率 Self- resonant frequency (MHz)min.	直流电阻 DC resistance (Ω) max.	额定电流 Rated current. (mA)max.	电感公差 Inductance tolerance
1	J-MRPC565040A-681X	680.0	20	0.796	2.20	10.000	100.0	±5%, ±10%
2	J-MRPC565040A-821X	820.0	20	0.796	2.00	13.000	90.0	±5%, ±10%
3	J-MRPC565040A-102X	1000.0	20	0.252	1.80	15.000	85.0	±5%, ±10%
4	J-MRPC565040A-122X	1200.0	20	0.252	1.50	17.000	75.0	±5%, ±10%
5	J-MRPC565040A-152X	1500.0	20	0.252	1.40	20.000	70.0	±5%, ±10%
6	J-MRPC565040A-182X	1800.0	20	0.252	1.30	30.000	60.0	±5%, ±10%
7	J-MRPC565040A-222X	2200.0	20	0.252	1.20	35.000	55.0	±5%, ±10%
8	J-MRPC565040A-272X	2700.0	20	0.252	1.10	55.000	45.0	±5%, ±10%
9	J-MRPC565040A-332X	3300.0	20	0.252	1.00	60.000	40.0	±5%, ±10%
10	J-MRPC565040A-392X	3900.0	20	0.252	1.00	70.000	38.0	±5%, ±10%
11	J-MRPC565040A-472X	4700.0	20	0.252	0.90	78.000	36.0	±5%, ±10%
12	J-MRPC565040A-562X	5600.0	20	0.252	0.80	85.000	33.00	±5%, ±10%
13	J-MRPC565040A-682X	6800.0	20	0.252	0.70	110.000	30.0	±5%, ±10%
14	J-MRPC565040A-822X	8200.0	20	0.252	0.60	125.000	28.0	±5%, ±10%
15	J-MRPC565040A-103X	10000.0	15	0.080	0.50	150.000	25.0	±5%, ±10%

Test remarks:

1.Rated current: Value obtained when current flows and the temperature has risen to 20°C or when DC current flows and the initial value of inductance has fallen by 10%, whichever is smaller

2.Test equipment L, Q: HP4285A +16034E, or equivalent.


3.SRF: HP8753C NETWORK ANALYZER, or equivalent.

4.DC resistance: AX-111A DIGITAL MILLIOHM METER, or equivalent.

客户名称 Customer	N/A	品名 Name	Plastic inductors	版本 Ver.	A00
客户型号 Model No.	N/A	料号 Material No.	N/A	日期 Date	2024.9.7
客户料号 Customer No.	N/A	型号 Model No.	MRPC565040 Series	发行号 Release No.	JS-S-24090703


5. 包装/PACKAGE :

(1) Tape Dimensions(Unit:mm)



W	AO	BO	KO	E	F	P	PO	DO	D1	T
16.0 ±0.3	5.35 ±0.1	6.10 ±0.1	4.5 ±0.1	1.75 ±0.1	7.5 ±0.1	12.0 ±0.1	4.0 ±0.1	1.5 ±0.1	1.5 ±0.3	0.35 ±0.05

(2) Reel Dimensions (Unit:mm)




规格Type	A	B	C	D	G	N	T
13"	330 Ref	23 Ref	13 Ref	16 Ref	17.5 Max	100 Min	22.4 Max

(3) Packaging Quantity (Unit:Pcs)

盘包装Reel	内盒Inner Box (mm)	外箱Outer Box (mm)
1000 支/盘pieces/Reel	4000支/盒pieces/Inner Box	16000支/箱pieces/Outer Carton


客户名称 Customer	N/A	品名 Name	Plastic inductors	版本 Ver.	A00
客户型号 Model No.	N/A	料号 Material No.	N/A	日期 Date	2024.9.7
客户料号 Customer No.	N/A	型号 Model No.	MRPC565040 Series	发行号 Release No.	JS-S-24090703

6. 建议回流焊温度曲线/Reflow temperature profile is recommended:




客户名称 Customer	N/A	品名 Name	Plastic inductors	版本 Ver.	A00
客户型号 Model No.	N/A	料号 Material No.	N/A	日期 Date	2024.9.7
客户料号 Customer No.	N/A	型号 Model No.	MRPC565040 Series	发行号 Release No.	JS-S-24090703

7. 可靠性测试/Reliability Test:

项目 Requirements	试验条件 Test method	性能要求 Characteristics																					
高温试验 High TEMP life test	温度: 125±3℃; 放置时间: 1000±6Hrs; TEMP. 125±3℃, Load 1000±6Hrs.	外观无显著异常; 电感值变化率: ±10%以内; Inductance change : Within ±10%; No significant abnormality in appearance.																					
低温试验 Low TEMP life test	温度: -40±2℃; 放置时间: 1000±6Hrs; TEMP. -40±2℃, Load 1000±6Hrs	外观无显著异常; 电感值变化率: ±10%以内; Inductance change : Within ±10%; No significant abnormality in appearance.																					
高湿试验 Damp heat	温度: 40±2℃, 相对湿度90~95%RH; 放置时间: 1000±6Hrs; TEMP. 40±2℃, Humidity. 90 ~ 95%RH, Load 1000±6Hrs	外观无显著异常; 电感值变化率: ±10%以内; Inductance change : Within ±10%; No significant abnormality in appearance.																					
热冲击试验 Thermal shock	将试验品焊接到印刷线路板上,按下表所示循环步骤,10个循环 <table><tr><th colspan="3">1个循环条件Conditions of 1 cycle</th></tr><tr><th>步骤 Step</th><th>温度 (℃) TEMP</th><th>时间 (min) Duration</th></tr><tr><td>1</td><td>-40±3</td><td>30±3</td></tr><tr><td>2</td><td>常温</td><td>3以下</td></tr><tr><td>3</td><td>+125±2</td><td>Within 3</td></tr><tr><td>4</td><td>常温</td><td>3以下</td></tr><tr><td></td><td>Room TEMP</td><td>Within 3</td></tr></table>	1个循环条件Conditions of 1 cycle			步骤 Step	温度 (℃) TEMP	时间 (min) Duration	1	-40±3	30±3	2	常温	3以下	3	+125±2	Within 3	4	常温	3以下		Room TEMP	Within 3	外观无显著异常; 电感值变化率: ±10%以内; Inductance change : Within ±10%; No significant abnormality in appearance.
1个循环条件Conditions of 1 cycle																							
步骤 Step	温度 (℃) TEMP	时间 (min) Duration																					
1	-40±3	30±3																					
2	常温	3以下																					
3	+125±2	Within 3																					
4	常温	3以下																					
	Room TEMP	Within 3																					
端子强度试验 Adhesion of terminal electrode	试验品焊接到试验用印刷线路板上,施加力9.8N(1kg),施加时间10±2sec,方向: X、Y The test samples shall be soldered to the test board by the reflow. 	外观无显著异常; 电感值变化率: ±10%以内; Inductance change : Within ±10%; No significant abnormality in appearance.																					
耐振性 Resistance to vibration	将产品焊接到印刷线路板上,按下示条件进行测试: 振动频率范围: 10~55Hz; 振幅: 1.5mm (但加速度不能超过196m/s²); 1个循环: 1分钟 (10→55→10Hz); 时间: X、Y、Z方向各2小时 The test samples shall be soldered to the test board by the reflow. Then it shall be submitted to below conditions. Frequency Range:10~55Hz; Total Amplitude :1.5mm (May not exceed acceleration 196m/s²); Sweeping Method: 10→55→10Hz for 1min Time: For 2 hours on each X, Y, and Z axis.	外观无显著异常; 电感值变化率: ±10%以内; Inductance change : Within ±10%; No significant abnormality in appearance.																					

客户名称 Customer	N/A	品名 Name	Plastic inductors	版本 Ver.	A00
客户型号 Model No.	N/A	料号 Material No.	N/A	日期 Date	2024.9.7
客户料号 Customer No.	N/A	型号 Model No.	MRPC565040 Series	发行号 Release No.	JS-S-24090703

7. 可靠性测试/Reliability Test:

抗弯强度试验 Resistance to flexure of substrate	将试验品焊接到试验用印刷线路板上，如图所示在印刷线路板上按箭头方向施加荷重，使其弯曲 2mm 为止。 The test samples shall be soldered to the test board by the reflow. Then apply a force in the direction shown below, flexure: 2mm. 	外观无显著异常，无破损； 电感值变化率：±10%以内； Inductance change: Within ±10%; No significant abnormality in appearance, No damage.
可焊性试验 Solderability	焊锡温度：250±5℃ 浸渍时间：5±0.5ses 浸渍深度：安装端子面浸入。 Solder Temperature:250±5℃ Time: 5±0.5ses All sides of mounting terminal shall be immersed.	端电极新锡覆盖面积达95%以上 At least 95% of surface of terminal electrode is covered by new solder.
耐焊接热试验 Resistance to soldering heat	方法1：将端子在250±5℃的焊液中浸入10±1秒后常温放置2小时以上 Method 1: Immerse in the solder of 250±5℃ for 10±1sec, load in room Temperature 2 hours. 方法2：峰值温度 250℃保持 20-40 秒回流焊接两遍试验，放置 30 分钟后检测（Per MIL-STD-202F） Method 2: The test sample shall be exposed to reflow with peak temperature at 250℃ for 20 to 40 seconds, 2 times. Load in room Temperature 30 min. (Per MIL-STD-202F)	外观无显著异常； 电感值变化率：±10%以内； Inductance change: Within ±10%; No significant abnormality in appearance.
温度特性 Temperature characteristic	在-40℃～+125℃环境温度范围内测试，并以20℃时的值为基准计算得出。 步骤1～5中最大电感值偏差变化率： 步骤1的温度：20℃ 步骤2的温度：最低使用温度 步骤3的温度：20℃（基准温度） 步骤4的温度：最高使用温度 步骤5的温度：20℃ Measurement of inductance shall be taken at temperature range within -40℃～+125℃. With reference to inductance value at +20℃., change rate shall be calculated. Change of maximum inductance deviation in step 1 to 5: Temperature at step 1: 20℃ Temperature at step 2: Minimum operating temperature Temperature at step 3: 20℃ (Standard temperature) Temperature at step 4 :Maximum oparating temperature Temperature at step 5 :20℃	外观无显著异常； 电感值变化率：±20%以内； Inductance change: Within ±20%; No significant abnormality in appearance.
跌落试验 Dropping	包装 OK 的产品，1m 高/木质地板或水泥地板，三次。 Packing ok product, Dropping 1m over the ground of concrete or cement, 3 times.	外观无显著异常，无破损； 电感值变化率：±10%以内； Inductance change: Within ±10%; No significant abnormality in appearance, No damage.

* 测定条件：如无特别指定时，其温度为 20±15℃，湿度为 65±20%。如在判定上如出现疑问时，可变更为 20±2℃，湿度为 65±5%。
如无特别指定时，试验后在常温、常湿中放置 1 小时以上，2 小时内测定。